



## VTrak E5000 Series Data Sheet



16Gb Fibre Channel to 12Gb SAS/SATA  
High-Availability Storage System for Big Data



### Benefits

- ▶ High-performance, high-bandwidth allowing more than 12.8 GB/s aggregate transfer rate
- ▶ High-Availability provides assurance of continuous operation
- ▶ Active-Active Dual Controller with ALUA for performance and access flexibility
- ▶ Virtualization Ready
- ▶ 80 PLUS GOLD certified PSUs, Deliver power efficiency, and Energy Star Ready
- ▶ Advanced diagnostics and reporting with persistent error log
- ▶ Support massive capacity by cascading up to 9 J5000 12Gb or SAS/SATA JBOD Storage Expansions

### Tech Highlights

- ▶ Quad 16 Gb FC ports per Controller provides maximum bandwidth
- ▶ 12 Gb SAS backend storage interface to support the fastest HDD/SSD
- ▶ Backward compatible to 8 Gb and 4 Gb on Fibre Channel interface, and to 6 Gb on SAS/SATA interface
- ▶ Conveniently accessible persistent error logging and HTML formatted Service Report
- ▶ Online Capacity Expansion allows Volume size to grow with ease
- ▶ Software Updates without disrupting operation
- ▶ Background Data Integrity Checking and Parity Rebuild
- ▶ Predictive Data Migration (PDM) minimizes maintenance requirement

### Affordable Enterprise-level Storage

Delivers an affordable high-performance Fibre Channel to SAS Storage solution with advanced enterprise level reliability and functionality.

Four 16Gb Fibre Channels ports and Two 12Gb SAS port (SFF-8644) per controller for connecting Host and Storage Expansion, respectively. Perfect for applications requiring huge bandwidth.

Redundant and Active-Active components of controllers, power supplies, and cooling units providing optimal data availability for any unforeseen circumstance.

Full featured Enterprise-level Storage System to accommodate any size of business environment.

### IT/Data Center Ready

The ability to deploy 6/12 Gb SAS/SATA hard drives and SSDs in the E5000 Series.

Efficient power supplies provide up to 90% power efficiency that improves TCO by conserving power, reducing heat output and improving cooling costs.

Flash arrays enable optimized speed for key enterprise applications that need High-speed transfer rate and reduced latency.

Intel multi-cores processors allows saturation of line rate speeds for both 16Gb Fibre Channel Front-end and 12Gb SAS Backend interfaces.

Delivers high capacity for archiving and backup




Transport feature allows portability to move and/or store Petabytes from one location to another with data intact

### Virtualization Ready

Ready to confront any challenge in today's virtualized IT environment, the VTrak E5000 Series is certified with VMware vSphere, Citrix XenServer, Microsoft Hyper-V, Veeam, and DataCore SANsymphony.

Virtualization enables dynamic storage allocations such that physical layers of storage can be utilized most effectively. As virtual machines continue to increase with more virtualized deployments, 16Gb Fibre Channel performance delivers the faster bandwidth needed for growing infrastructures.

## Technical Specifications

VTrak E5300f		VTrak E5600f		VTrak E5800f		
Models	2U/12 Bay 		3U/16 Bay 		4U/24 Bay 	
Drive Support	Up to 12 3.5" drives		Up to 16 3.5" drives		Up to 24 3.5" drives	
	6/12 Gb SAS, 6 Gb SATA HDD and SSD Supports any mix of SAS and SATA drives simultaneously in the same enclosure					
External I/O Ports	Each SBB2.0 RAID Controller has four 16 Gb FC SFP ports for Host interface and two 12 Gb SAS standard Mini SAS HD ports (SFF-8644) for Storage Expansion, RJ45 1Gb Ethernet and RS232 for Management ports					
Operational Features						
RAID Levels	0, 1, 5, 6, 10, 50, 60					
RAID Stripe Size Support	64K, 128K, 256K, 512K and 1MB					
Hot Spares	Global or dedicated with revertible option					
Max LUNs per Subsystem	1024					
Max Luns per array	32					
Advanced Storage Features	<ul style="list-style-type: none"><li>Advanced Cache Mirroring over PCIe Gen3</li><li>Simple, drag-and-drop LUN Masking and Mapping</li><li>Asymmetric LUN Unit Access (ALUA)</li><li>Volume Copy</li></ul>		<ul style="list-style-type: none"><li>PerfectFlash - Non-Disruptive Software Update</li><li>I/O performance &amp; power monitoring tools</li><li>USB Service Log</li><li>LDAP Support for central user management</li></ul>			
Background Activities	<ul style="list-style-type: none"><li>Media Patrol</li><li>Background Synchronization</li><li>Foreground Initialization</li><li>Rebuild</li><li>Redundancy Check</li></ul>		<ul style="list-style-type: none"><li>Disk SMART Polling</li><li>Online Capacity Expansion (OCE)</li><li>RAID Level Migration (RLM)</li><li>UPS Monitoring</li><li>Feature rich task scheduler for background activities</li></ul>			
PerfectRAID Features	<ul style="list-style-type: none"><li>Predictive Data Migration (PDM)</li><li>Intelligent Bad Sector Remapping</li><li>SMART Error Handling</li><li>NVRAM Error Logging</li></ul>		<ul style="list-style-type: none"><li>Disk Slot Power Control</li><li>Read/Write Check Table</li><li>Write Hole Table</li></ul>			
GreenRAID Features	<ul style="list-style-type: none"><li>Four levels of advanced power management disk drive (MAID) support</li><li>Efficient 80Plus Certified power supplies</li></ul>					
System Management						
Management Interfaces	<ul style="list-style-type: none"><li>Web Based management using WebPAM PROe (Ethernet)</li><li>Command Line Interface (CLI) or Command Line Utility (Serial Port or Ethernet via Telnet, SSH)</li><li>Third Party Management Support via SNMP, CIM</li></ul>					
Supported OSs	Windows Server 2008, 2012, OS X 10.x, RHEL 6.5, 6.6, 6.7, and 7.2, SLES 11, 11 SP4, and 12 SP1					
Software Certification	VMware ESXi 6.0, VEEAM Backup & Replication 9.0, Citrix Server 7.0, Data Core SANSymphony 10.0 PSP6, Windows, Arcserve UDP v6.0.3792 Update 3 Build 776, XSAN 5, StorNext v5.3					
Mechanical Specifications						
Voltage	100--240 Vac Auto--Ranging					
Current (Maximum)	9A @ 100 Vac; 4A @ 240 Vac					
Power Conversion Efficiency	>80% @ 110V (>20% load), >80% @ 240V (>20% load) Temperature Range					
Temperature Range	Operational: 5° to 35°C, Non-Operational: -40° to 60°C					
Humidity	Operational: 20% to 80% (Non-Condensing), Non--Operational: ~ 95% (Non-Condensing)					
Acoustic Noise Levels	< 60dB, 25C					
Shock	Operational: 5G, 11 ms duration, Non-Operational: 30G, 11ms duration					
Vibration	Operational: 0.2G, 5 to 500Hz (sine wave) ; 0.41G, 3-10-200-500Hz (Random) , Non-Operational: 1G, 5 to 500Hz (sine wave) ; 2.256G, 5-80-350-500Hz (Random)					
Environmental Standards	RoHS, GreenPC, WEEE					
Power Supply	Efficient 80PLUS GOLD Certified redundant PSU					
Dimensions (H x W x D)	88 x 446.7 x 507 mm		88 x 446.7 x 507 mm		88 x 446.7 x 507 mm	
Weight	18.9Kg (41.7 lbs) w/o drives 26.8Kg (59.1 lbs) w/ drives		23Kg (50.7 lbs) w/o drives 33.4Kg (73.6 lbs) w/ drives		24.8Kg (54.7 lbs) w/o drives 40.5Kg (89.2 lbs) w/ drives	
Warranty and Support						
Warranty	3-year full system limited warranty, optional extended warranty, onsite parts replacement program					
Support	24/7 e-mail and phone support, 24/7 access to PROMISE site-drives, firmware, and compatibility list					

SATA drives require a SAS-SATA adapter

